

## FEATURES



**Model 300AT**

### **A. BACK AND SEAT**

Injection molded polypropylene plastic with textured surface. Compound curved seat provides waterfall edge. Back has a natural flex mechanism due to the design, overall frame construction, and the materials used; resistance increases responding to pressure from the user's weight.

### **B. BASE AND FRAME**

Sled base with optional non marring glides (GSN option). Chrome nickel plated 1/2" solid steel wire frame with two 1/2" diameter solid steel wire cross members; one 10-gauge strap and two 11-gauge straps are provided for seat mounting—results in improved structural integrity and back/seat/leg reinforcement and recessed cross bar for leg clearance.

### **C. TABLET ARM OPTION**

Field mountable on either left or right side (must be specified at time of ordering). Constructed of 3/4" thick plywood board with black high pressure laminate finish and hinged—arm pivots/folds/flips out of the way for easy seating access. Special laminate colors available upon request.

### **D. STACKING AND GANGING**

Stacks 45 high on #30D Dolly and ganging glides (GHG option). Stacks 10 high on the floor—Upholstered models come complete with separators to prevent damage to fabric and foam. Stacks 18 high on dolly when upholstered.

*Note: multiple aesthetic and functional options available.*

## DIMENSIONS

### Model 308

<b>Overall Width</b> (Outer armrest to outer armrest)	19"
<b>Overall Depth</b> (Front seat to back of back rest)	22.5"
<b>Overall Height</b> (Floor to top of back rest)	32.25"
<b>Seat Width</b>	18"
<b>Back Width</b>	16.5"
<b>Back Height</b> (From compressed seat)	17"
<b>Seat Height</b>	18"
<b>Seat Depth</b>	18"



### Model 300AT

<b>Overall Width</b> (Outer armrest to outer armrest)	20"
<b>Overall Depth</b> (Front seat to back of back rest)	22.5"
<b>Overall Height</b> (Floor to top of back rest)	32.25"
<b>Seat Width</b>	18"
<b>Back Width</b>	16.5"
<b>Back Height</b> (From compressed seat)	17"
<b>Seat Height</b>	18"
<b>Seat Depth</b>	18"

